



**HILLCREST** INTERIOR TRIM INCLUDED

HANDING	MODEL #	DESCRIPTION
^R/L	2810	Single Cylinder
^R/L	2815	Single Cylinder (Dummy)

^Handing required when ordering a New Haven lever.




**PARKSIDE** INTERIOR TRIM INCLUDED

HANDING	MODEL #	DESCRIPTION
^R/L	2820	Single Cylinder
^R/L	2825	Single Cylinder (Dummy)

^Handing required when ordering a New Haven lever.

**GENERAL SPECIFICATIONS**

PRODUCT CATEGORY	CYLINDER		STRIKES		FACEPLATES		DOOR HANDING	ADA	ANSI	UL	BORING REQUIREMENTS				DOOR THICKNESS		BACKSET	LATCH BOLT THROW	
	STANDARD	OPTIONAL	DEADBOLT	HANDLE	STANDARD	OPTIONAL					CROSS BORE		EDGE BORE	LATCH FACE	STANDARD	SPECIAL		DEADBOLT	HANDLE
											DEADBOLT	HANDLE							
Handlesets (Hillcrest, Parkside)	5 Pin Weslock Keyway	5 Pin Schlage Cor Kwikset Keyway	2-1/4" full lip and 1" x 2-1/4" no lip, Radius (Square Optional)	2-1/4" full lip, Radius (Square Optional)	1" x 2-1/4" Fixed Radius	1" x 2-1/4" Fixed Square or Drive-in	Specify handing for New Haven lever, for all others reversible for right or left-hand doors	N/A	A 156.2 Grade III	N/A	2-1/8" or 1-5/8"	2-1/8"	1"	1" x 2-1/4"	1-3/8"-1-3/4"	N/A	Deadbolt Adjustable 2-3/8" or 2-3/4" Springlatch Non-Adjustable 2-3/8" or 2-3/4"	1"	1/2"



MODEL	A	B	C	D	E
Hillcrest	2-1/2"	*5-1/2"	8-7/16"	17"	2-7/8"
Parkside	2-1/2"	*5-1/2"	8-7/16"	17"	2-5/8"

\*5-1/4" minimum

**CLASSIFICATION KEY**

- A - Projection from Door
- B - Center to Center
- C - Footscrew
- D - Full Length
- E - Width of Rose (Escutcheon Plate)